



Speedifix



The quickest lightweight modular platform to assemble.



Specifications

Length	Configuration	platform weight	H400		Skymax 500		OCTO 800	
			S.W.P.	S.W.L.	S.W.P.	S.W.L.	S.W.P.	S.W.L.
2m	2	140 kg	275 kg	260 kg	305 kg	260 kg	350 kg	260 kg
3m	3	160 kg	295 kg	390 kg	325 kg	390 kg	370 kg	390 kg
4m	2+2	200 kg	335 kg	465 kg	365 kg	520 kg	410 kg	520 kg
5m	3+2	220 kg	355 kg	335 kg	390 kg	615 kg	430 kg	645 kg
6m	3+3	240 kg	375 kg	295 kg	410 kg	465 kg	450 kg	775 kg
6m WTS	1*2+2*1	380 kg					590 kg	515 kg
7m	2+2+3	280 kg	415 kg	250 kg	450 kg	385 kg	490 kg	900 kg
7m WTS	1*2+3*1	400 kg					610 kg	645 kg
8m	3+2+3	300 kg	440 kg	235 kg	470 kg	355 kg	510 kg	1030 kg
8m WTS	1*3+3*1	420 kg					630 kg	650 kg
9m	3+3+3	320 kg	460 kg	220 kg	490 kg	330 kg	530 kg	980 kg
9m WTS	1*2+3+2*1	460 kg					670 kg	555 kg
10m	3+2+2+3	360 kg	500 kg	190 kg	530 kg	300 kg	570 kg	730 kg
10m WTS	2*3+3*2	465 kg					675 kg	440 kg
11m	3+3+3+2	380 kg	520 kg	180 kg	551 kg	280 kg	590 kg	570 kg
11m WTS	2*2+3+2*2	505 kg					715 kg	420 kg
12m	3+3+3+3	405 kg	540 kg	165 kg	570 kg	265 kg	610 kg	460 kg
12m WTS	2*3+2+3*2	530 kg					735 kg	410 kg
13m WTS	2*3+3+3*2	550 kg					755 kg	400 kg
14m WTS	2*3+2+2+3*2	590 kg					800 kg	380 kg
15m WTS	2*3+2+3+3*2	610 kg					820 kg	370 kg
16m WTS	2*3+3+3+3*2	630 kg					840 kg	360 kg

S.W.P. includes; hoist, Safety Brake, supports, wall & castor rollers, 55m power supply cable, overloads, central control box and 50m steel wire ropes